



ALGAE

696-00101032955a


ALGAE L PD SUSPENSION made of aluminium, white, similar to RAL 9016, anti-glare LFO lens due to microfacetted structure beam 55°, light output direct, with converter, max. 350mA, dimmable 1-10V, cable white, soft-touch, adapter/ceiling base white, pendant length 1500mm, IP20



DRAWING



LIGHT DISTRIBUTION CURVE



TECHNICAL DETAILS

System perform. [W]	15
Bulb type	LED
Luminous flux [lm]	760
Current sec. [mA]	350
Colour temp. [K]	3000K
CRI	>90
Optics	LFO lens
Designer	Rainer Mutsch
Dimming	1-10V
Light output	direct
Beam angle [°]	55°
Voltage [V]	220-240V 50/60Hz
Material	aluminium

Length [mm]	140
Height [mm]	975
Pendant length [mm]	1500
Diameter [mm]	230
IP protection class	IP20
Voltage class	protection cl. I
Net weight [kg]	2,21

Color lamp	white
RAL	9016
Color adapter/ceiling base	white
Electric wire	white, soft-touch
EAN-Number	9010506000450
Lifetime [h]	L80 B10 50 000
No. of luminaires B16A	50



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.